


KINGDOM OF SAUDI ARABIA
AL-IMAM MUHAMMAD BIN SAUD
ISLAMIC UNIVERSITY
FACULTY OF SCIENCES
DEPARTMENT OF PHYSICS



المملكة العربية السعودية
جامعة الإمام محمد بن سعود الإسلامية
كلية العلوم
قسم الفيزياء

Electromagnetic Field (PHY 321)



Dr. Naglaa Abdel All

1445 / 2024



Chapter1 : Vector Analysis

Reference book:

Sadiku M., *Elements of Electromagnetic*, 2nd Edition, Saunders College (1995).

1- Vector Multiplication

ضرباً المتجهية

1-1- Scalar Product (or dot product)

Consider $\vec{A} = A_x \vec{a}_x + A_y \vec{a}_y + A_z \vec{a}_z$ and $\vec{B} = B_x \vec{a}_x + B_y \vec{a}_y + B_z \vec{a}_z$. We define the scalar product (or dot product) of vectors $\vec{A}$ and $\vec{B}$ as

گذاشته

$$\vec{A} \cdot \vec{B} = |\vec{A}| |\vec{B}| \cos \theta \quad \text{where } \theta \text{ is the smaller angle between } \vec{A} \text{ and } \vec{B}$$

We can prove that $\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z$

$$\vec{a}_x \cdot \vec{a}_x = \vec{a}_y \cdot \vec{a}_y = \vec{a}_z \cdot \vec{a}_z = 1$$

$$\vec{a}_x \cdot \vec{a}_y = \vec{a}_x \cdot \vec{a}_z = \vec{a}_y \cdot \vec{a}_z = 0$$

$$\vec{a}_x \times \vec{a}_x = \vec{a}_y \times \vec{a}_y = \vec{a}_z \times \vec{a}_z = 0$$

$$\vec{a}_x \times \vec{a}_y = \vec{a}_z$$

$$\vec{a}_y \times \vec{a}_z = \vec{a}_x$$

$$\vec{a}_z \times \vec{a}_x = \vec{a}_y$$

1-2- Vector Product (or Cross Product)

We define the vector product of vectors $\vec{A}$ and $\vec{B}$ as

$$\vec{A} \times \vec{B} = |\vec{A}| |\vec{B}| \sin \theta \vec{a}_n$$

where $\vec{a}_n$ is a unit vector (i.e., $|\vec{a}_n| = 1$) normal to the plane containing $\vec{A}$ and $\vec{B}$.

$$\vec{A} \times \vec{B} = \begin{vmatrix} \vec{a}_x & \vec{a}_y & \vec{a}_z \\ A_x & A_y & A_z \\ B_x & B_y & B_z \end{vmatrix}$$
$$\vec{A} \times \vec{B} = (A_y B_z - A_z B_y) \vec{a}_x - (A_x B_z - A_z B_x) \vec{a}_y + (A_x B_y - A_y B_x) \vec{a}_z$$

$$\vec{A} = A_x \hat{a}_x + A_y \hat{a}_y + A_z \hat{a}_z \quad (A_x, A_y, A_z)$$

$$A = 3\hat{a}_x + 2\hat{a}_y + 4\hat{a}_z \quad (3, 2, 4)$$

ضرب المتجهات

ضرب قياسي

scalar product


$\vec{A} \cdot \vec{B} =$ الناتج عدد

$$\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z$$

$$\vec{A} = 3\hat{a}_x + 2\hat{a}_y - 5\hat{a}_z$$

$$\vec{B} = 2\hat{a}_x - \hat{a}_y + 2\hat{a}_z$$

$$\begin{aligned} \vec{A} \cdot \vec{B} &= 3 \cdot 2 + 2(-1) + (-5)2 \\ &= 6 - 2 - 10 \\ &= -6 \end{aligned}$$



$$\vec{A} \cdot \vec{B} = |\vec{A}| |\vec{B}| \cos \theta$$

$$A \cdot B = 3 \cdot 4 \cdot \cos 60^\circ = 6$$


$$\hat{a}_x \cdot \hat{a}_x = \hat{a}_y \cdot \hat{a}_y = \hat{a}_z \cdot \hat{a}_z = 1$$

$$\hat{a}_x \cdot \hat{a}_y = \hat{a}_y \cdot \hat{a}_z = \hat{a}_z \cdot \hat{a}_x = 0$$

الضرب الاتجاهي

cross product

$\vec{A} \times \vec{B} =$ الناتج متجه متعامد عمودي على المتجهين



$$|\vec{A} \times \vec{B}| = |\vec{A}| |\vec{B}| \sin \theta$$

$$\vec{A} \times \vec{B} = \begin{vmatrix} \hat{a}_x & \hat{a}_y & \hat{a}_z \\ A_x & A_y & A_z \\ B_x & B_y & B_z \end{vmatrix}$$

$$\vec{A} = 2\hat{a}_x + \hat{a}_y - 2\hat{a}_z$$


$$\vec{B} = 3\hat{a}_x + \hat{a}_y + \hat{a}_z$$

$$\begin{vmatrix} \hat{a}_x & \hat{a}_y & \hat{a}_z \\ 2 & 1 & -2 \\ 3 & 1 & 1 \end{vmatrix}$$

$$= (1+2)\hat{a}_x - (2+6)\hat{a}_y$$

$$(2-3)\hat{a}_z$$

$$= 3\hat{a}_x - 8\hat{a}_y - \hat{a}_z$$




$$\hat{a}_x \times \hat{a}_y = \hat{a}_y \times \hat{a}_z = \hat{a}_z \times \hat{a}_x = 0$$

$$\hat{a}_x \times \hat{a}_y = \hat{a}_z \quad \hat{a}_y \times \hat{a}_z = \hat{a}_x$$

2- Coordinate Systems and Transformations

2-1- Cartesian Coordinates (x,y,z)

A point P can be represented as (x,y,z)



The ranges of the coordinate variables x, y, and z are

$$-\infty < x < \infty$$

$$-\infty < y < \infty$$

$$-\infty < z < \infty$$

A vector $\vec{A}$ in Cartesian coordinates can be written as

$$\vec{A} = (A_x, A_y, A_z) \quad \text{or} \quad \vec{A} = A_x \vec{a}_x + A_y \vec{a}_y + A_z \vec{a}_z$$

2-2- Circular Cylindrical Coordinates (ρ, ϕ, z)

A point P in cylindrical coordinates is represented as (ρ, ϕ, z) and is as shown in Figure

3. ρ is the radius of the cylinder passing through P or the radial distance from the z-axis.


Φ called the azimuthal angle, is measured from the x-axis in the xy-plane; and z is the

same as in the Cartesian system.

$$0 \leq \rho < \infty$$

$$0 \leq \phi < 2\pi$$


$$-\infty < z < \infty$$



Cartesian coordinate system (x, y, z)

$$\vec{A} = A_x \hat{a}_x + A_y \hat{a}_y + A_z \hat{a}_z$$


$$(A_x, A_y, A_z)$$



Cylindrical coordinate system (ρ, φ, z)


$$\vec{A} = A_\rho \hat{a}_\rho + A_\phi \hat{a}_\phi + A_z \hat{a}_z$$

φ: Azimuthal



Spherical coordinate system (r, φ, θ)

θ: Colatitude



Differential element in length

المتغيرات	المتجه	$dr = dl$
(x, y, z)	$\vec{r} = x\hat{a}_x + y\hat{a}_y + z\hat{a}_z$	$dr = dl = dx\hat{a}_x + dy\hat{a}_y + dz\hat{a}_z$
(ρ, φ, z)	$\vec{r} = \rho\hat{a}_\rho + z\hat{a}_z$	$dr = dl = d\rho\hat{a}_\rho + \rho d\phi\hat{a}_\phi + dz\hat{a}_z$
(r, φ, θ)	$\vec{r} = r\hat{a}_r$	$dr = dl = dr\hat{a}_r + r d\theta\hat{a}_\theta + r \sin\theta d\phi\hat{a}_\phi$

2-3- Spherical Coordinates System

A point P can be represented as (r, θ, ϕ) and is illustrated in Figure 6. From Figure 6, we notice that r is defined as the distance from the origin to point P or the radius of a sphere centered at the origin and passing through P ; θ (called the colatitude) is the angle between the z -axis and the position vector of P ; and ϕ is measured from the x -axis (the same azimuthal angle in cylindrical coordinates).




Figure 6.


$$0 \leq r < \infty$$

$$0 \leq \theta \leq \pi$$


$$0 \leq \phi < 2\pi$$

3- Vector position and Differential element in length

Consider a point P located in space, and consider the direct arrow extending from the origin to this point P . This arrow is known as the position vector $\vec{r}$. A position vector is an alternative way to denote the location of a point P in space.





$$\text{مثال: } \Delta \vec{r} = \vec{r}_2 - \vec{r}_1$$



3. 1- Vector position, $\vec{r}$, and differential element in length, $d\vec{l}$, in Cartesian coordinates system:

$$\vec{r} = x\vec{a}_x + y\vec{a}_y + z\vec{a}_z$$



when $\vec{r}_2 - \vec{r}_1 = \Delta\vec{r} \rightarrow 0$ (i.e., $\Delta\vec{r} = d\vec{r} = d\vec{l}$),

$$d\vec{r} = d\vec{l} = dx\vec{a}_x + dy\vec{a}_y + dz\vec{a}_z$$

(1) Differential displacement is given by

(2) Differential normal area is given by

$$d\mathbf{S} = dy \, dz \, \mathbf{a}_x + dx \, dz \, \mathbf{a}_y + dz \, dy \, \mathbf{a}_z$$


(3) Differential volume is given by

$$dv = dx \, dy \, dz$$

3. 2- Vector position, $\vec{r}$, and differential element in length, $d\vec{l}$, in cylindrical coordinates system:

$$\vec{r} = \rho \vec{a}_\rho + z \vec{a}_z$$

$$d\vec{r} = d\vec{l} = d\rho \vec{a}_\rho + \rho d\phi \vec{a}_\phi + dz \vec{a}_z$$



(2) Differential normal area is given by


$$d\vec{S} = \begin{matrix} \rho d\phi dz \vec{a}_\rho \\ d\rho dz \vec{a}_\phi \\ \rho d\phi d\rho \vec{a}_z \end{matrix}$$

$$dv = \rho d\rho d\phi dz$$

3. 3- Vector position, $\vec{r}$, and differential element in length, $d\vec{l}$, in spherical coordinates system:

$$\vec{r} = r \vec{a}_r$$

$$d\vec{r} = d\vec{l} = dr \vec{a}_r + r d\theta \vec{a}_\theta + r \sin \theta d\phi \vec{a}_\phi$$



المختصات
(x, y, z)

المختبة

$$\vec{r} = x\hat{a}_x + y\hat{a}_y + z\hat{a}_z$$

Differential

normal area, volume

$$ds = dx dy \hat{a}_z$$

$$ds = dy dz \hat{a}_x$$

$$ds = dx dz \hat{a}_y$$

$$dV = dx dy dz$$

(r, φ, z)


$$\vec{r} = \rho\hat{a}_\rho + z\hat{a}_z$$

$$ds = \rho d\phi dz \hat{a}_\rho$$

$$ds = d\rho dz \hat{a}_\rho$$

$$ds = \rho d\phi d\rho \hat{a}_z$$

$$dV = \rho d\rho d\phi dz$$



4. Line integral

ریکا مل حصہ

By a line we mean the path along a curve in space. We shall use terms such as line, curve, path and contour interchangeably.

The line integral $\int_L \vec{A} \cdot d\vec{l}$ is the integral of the tangential component of $\vec{A}$ along curve L.

$$\int_L \vec{A} \cdot d\vec{l} = \int_a^b |\vec{A}| \cos \theta dl$$




Figure. Path of integration of vector field $\vec{A}$.


Given a vector field $\vec{A}$ and a curve L, we define the integral $\int_L \vec{A} \cdot d\vec{l} = \int_a^b |\vec{A}| \cos \theta dl$ as the integral of $\vec{A}$ around L (see Figure).

If the path of integration is a closed curve $\int_L \vec{A} \cdot d\vec{l}$ becomes a closed line integral $\oint_L \vec{A} \cdot d\vec{l}$

which is called the circulation of $\vec{A}$ around L.

دور ان گتہ حول ل

$$\oint \vec{A} \cdot d\vec{l} = \oint |\vec{A}| \cos \theta dl$$



5. Surface integral ψ (الشفق) ψ Flux

Given a vector field $\vec{A}$, continuous in a region containing the smooth surface S , we define the surface integral or the flux of $\vec{A}$ through S (see figure) as

$$\psi = \int_S |\vec{A}| \cos \theta dS = \int_S \vec{A} \cdot \vec{a}_n dS$$

$$\psi = \int \vec{A} \cdot \vec{a}_n dS = \int |\vec{A}| \cos \theta dS$$

or simply

$$\psi = \int_S \vec{A} \cdot d\vec{S}$$

where at any point on S , $\vec{a}_n$ is the unit normal to S .

سطح مغلق

$\vec{a}_n$: اعمودي

For a closed surface, the surface integral becomes

$$\psi = \oint_S \vec{A} \cdot d\vec{S}$$

which is referred to as the net outward flux of $\vec{A}$ from S .

الانتقال عبر سطح مغلق :- الشفق لكل الى الخارج

as the volume integral of the scalar ρ_v over the volume v .

تكامل الحجم

$$\int_v \rho_v dv \rightarrow \text{كثافة الحجم}$$




Figure. The flux of a vector field $\vec{A}$ through surface S

PRACTICE EXERCISE 3.2

$$\int \mathbf{A} \cdot d\mathbf{L}$$

Calculate the circulation of

$$(\rho, \phi, z)$$

$$\mathbf{A} = \rho \cos \phi \mathbf{a}_\rho + z \sin \phi \mathbf{a}_z$$

around the edge L of the wedge defined by $0 \leq \rho \leq 2$, $0 \leq \phi \leq 60^\circ$, $z = 0$ and shown in Figure 3.11.

Answer: 1.

$$\hat{\mathbf{a}}_\rho \cdot \hat{\mathbf{a}}_\rho = 1$$

$$\mathbf{a}_\rho \cdot \mathbf{a}_\phi = 0$$


$$\hat{\mathbf{a}}_\rho \cdot \hat{\mathbf{a}}_z = 0$$

$$\int \mathbf{A} \cdot d\mathbf{L}$$

0

$$\int (\rho \cos \phi \mathbf{a}_\rho + z \sin \phi \mathbf{a}_z) \cdot d\mathbf{L}$$

$$\int (\rho \cos \phi \hat{\mathbf{a}}_\rho) \cdot (d\rho \hat{\mathbf{a}}_\rho + \rho d\phi \hat{\mathbf{a}}_\phi + dz \hat{\mathbf{a}}_z)$$



$$\int_0^2 \rho \cos \phi d\rho + 0 + 0 = \cos \phi \int_0^2 \rho d\rho = \cos 60^\circ \left[\frac{\rho^2}{2} \right]_0^2$$

$$\frac{1}{2} \frac{1}{2} [2^2 - 0] = \frac{1}{4} [4] = 1$$

4. DEL OPERATOR

∇ del

The del operator, written ∇ , is the vector differential operator. In Cartesian coordinates,

$$\nabla = \frac{\partial}{\partial x} \mathbf{a}_x + \frac{\partial}{\partial y} \mathbf{a}_y + \frac{\partial}{\partial z} \mathbf{a}_z$$

This vector differential operator, otherwise known as the *gradient operator*, is not a vector in itself, but when it operates on a scalar function, for example, a vector ensues. The operator is useful in defining

1. The **gradient** of a scalar V , written as ∇V
2. The **divergence** of a vector $\mathbf{A}$, written as $\nabla \cdot \mathbf{A}$
3. The **curl** of a vector $\mathbf{A}$, written as $\nabla \times \mathbf{A}$
4. The **Laplacian** of a scalar V , written as $\nabla^2 V$

Gradient of scalar

∇V

تدل على اتجاه أكبر معدل معدل للزيادة في
الكمية الفيزيائية

(x, y, z)

* إحداثيات كارتيزية

$$\nabla V = \frac{\partial V}{\partial x} \hat{a}_x + \frac{\partial V}{\partial y} \hat{a}_y + \frac{\partial V}{\partial z} \hat{a}_z$$

(ρ, φ, z)

* إحداثيات اسطوانية

$$\nabla V = \frac{\partial V}{\partial \rho} \hat{a}_\rho + \frac{1}{\rho} \frac{\partial V}{\partial \phi} \hat{a}_\phi + \frac{\partial V}{\partial z} \hat{a}_z$$

* إحداثيات كروية

$$\nabla V = \frac{\partial V}{\partial r} \hat{a}_r + \frac{1}{r} \frac{\partial V}{\partial \theta} \hat{a}_\theta + \frac{1}{r \sin \theta} \frac{\partial V}{\partial \phi} \hat{a}_\phi$$

- The del Operator in cylindrical system from the definition of the gradient:

$$\vec{\nabla} = \frac{\partial}{\partial \rho} \vec{a}_\rho + \frac{1}{\rho} \frac{\partial}{\partial \phi} \vec{a}_\phi + \frac{\partial}{\partial z} \vec{a}_z$$

in cylindrical system

$$\vec{\nabla} f = \frac{\partial f}{\partial \rho} \vec{a}_\rho + \frac{1}{\rho} \frac{\partial f}{\partial \phi} \vec{a}_\phi + \frac{\partial f}{\partial z} \vec{a}_z$$

in cylindrical system

- The del Operator in spherical system from the definition of the gradient:

$$\vec{\nabla} f = \frac{\partial f}{\partial r} \vec{a}_r + \frac{1}{r} \frac{\partial f}{\partial \theta} \vec{a}_\theta + \frac{1}{r \sin \theta} \frac{\partial f}{\partial \phi} \vec{a}_\phi$$

in spherical system

and

$$\vec{\nabla} = \frac{\partial}{\partial r} \vec{a}_r + \frac{1}{r} \frac{\partial}{\partial \theta} \vec{a}_\theta + \frac{1}{r \sin \theta} \frac{\partial}{\partial \phi} \vec{a}_\phi$$

in spherical system

EXAMPLE 3.3

Find the gradient of the following scalar fields:

(a) $V = e^{-z} \sin 2x \cosh y$

(b) $U = \rho^2 z \cos 2\phi$

(c) $W = 10r \sin^2 \theta \cos \phi$

Solution:

$$\begin{aligned} \text{(a)} \quad \nabla V &= \frac{\partial V}{\partial x} \mathbf{a}_x + \frac{\partial V}{\partial y} \mathbf{a}_y + \frac{\partial V}{\partial z} \mathbf{a}_z \\ &= 2e^{-z} \cos 2x \cosh y \mathbf{a}_x + e^{-z} \sin 2x \sinh y \mathbf{a}_y - e^{-z} \sin 2x \cosh y \mathbf{a}_z \end{aligned}$$

$$\begin{aligned} \text{(b)} \quad \nabla U &= \frac{\partial U}{\partial \rho} \mathbf{a}_\rho + \frac{1}{\rho} \frac{\partial U}{\partial \phi} \mathbf{a}_\phi + \frac{\partial U}{\partial z} \mathbf{a}_z \\ &= 2\rho z \cos 2\phi \mathbf{a}_\rho - 2\rho z \sin 2\phi \mathbf{a}_\phi + \rho^2 \cos 2\phi \mathbf{a}_z \end{aligned}$$

$$\begin{aligned} \text{(c)} \quad \nabla W &= \frac{\partial W}{\partial r} \mathbf{a}_r + \frac{1}{r} \frac{\partial W}{\partial \theta} \mathbf{a}_\theta + \frac{1}{r \sin \theta} \frac{\partial W}{\partial \phi} \mathbf{a}_\phi \\ &= 10 \sin^2 \theta \cos \phi \mathbf{a}_r + 10 \sin 2\theta \cos \phi \mathbf{a}_\theta - 10 \sin \theta \sin \phi \mathbf{a}_\phi \end{aligned}$$

Find the gradient

a) $V = e^{-z} \sin 2x \cosh y$

$$\nabla V = \frac{\partial V}{\partial x} \hat{a}_x + \frac{\partial V}{\partial y} \hat{a}_y + \frac{\partial V}{\partial z} \hat{a}_z$$

$$\nabla V = 2e^{-z} \cos 2x \cosh y \hat{a}_x + e^{-z} \sin 2x \sinh y \hat{a}_y - e^{-z} \sin 2x \cosh y \hat{a}_z$$

(b) $U = \rho^2 \cos 2\phi$

$$\nabla U = \frac{\partial U}{\partial \rho} \hat{a}_\rho + \frac{1}{\rho} \frac{\partial U}{\partial \phi} \hat{a}_\phi + \frac{\partial U}{\partial z} \hat{a}_z$$

$$\nabla U = 2\rho z \cos 2\phi \hat{a}_\rho - 2z \sin 2\phi \hat{a}_\phi + \rho^2 \cos 2\phi \hat{a}_z$$

$$\nabla U = 2\rho z \cos 2\phi \hat{a}_\rho - 2z \sin 2\phi \hat{a}_\phi + \rho^2 \cos 2\phi \hat{a}_z$$

$2 \sin x \cos x = \sin 2x$


(c) $W = 10 r \sin^2 \theta \cos \phi$

$$\nabla W = \frac{\partial W}{\partial r} \hat{a}_r + \frac{1}{r} \frac{\partial W}{\partial \theta} \hat{a}_\theta + \frac{1}{r \sin \theta} \frac{\partial W}{\partial \phi} \hat{a}_\phi$$

$$\nabla W = 10 \sin^2 \theta \cos \phi \hat{a}_r + \frac{2}{r} 10 r \sin \theta \cos \phi \hat{a}_\theta - \frac{1}{r \sin \theta} 10 r \sin^2 \theta \sin \phi \hat{a}_\phi$$

$$\nabla W = 10 \sin^2 \theta \cos \phi \hat{a}_r + 20 \sin \theta \cos \phi \hat{a}_\theta - 10 \sin \theta \sin \phi \hat{a}_\phi$$

Fields



Many physical quantities have different values at different points in space. For example, the temperature in the kitchen is different at different points: high near an electric furnace, low near an open window, and so on. The electric field around a point charge is large near the charge and decreases as we go away from the charge. In all these examples there is a particular region of space which is of interest for the problem at hand; at every point of this region some physical quantity has a value. The term field is used to mean both the region and the value of the physical quantity in the region. If the physical quantity is a scalar (for example, the temperature), we speak of a scalar field. If the quantity is a vector (for example, electric field), we speak of a vector field.

Directional derivative; Gradient

Suppose that we know the temperature $T(x,y,z)$ at every point of a room. Starting at a given point (x_0, y_0, z_0) we could ask for the rate of change of the temperature with distance (in degrees per centimeter) as we move away from the starting point (x_0, y_0, z_0) . The rate of change of temperature with distance depends upon the direction in which we move. In symbols, we want to find the limiting value of $\frac{\Delta T}{\Delta s}$ where Δs is an element of distance in a given direction, and ΔT is the corresponding change in temperature; we write the directional derivative as $\frac{dT}{ds}$.

Let us now state and solve the general problem of finding a directional derivative.


$$(x_0, y_0, z_0) \xrightarrow[S \hat{u}]{s} (x, y, z)$$

We are given a scalar field, that is, a function $f(x,y,z)$. We want to find $\frac{df}{ds}$ the rate of

change of f with distance, at a given point (x_0, y_0, z_0) and in a given direction. Let

$\vec{u} = u_1 \vec{a}_x + u_2 \vec{a}_y + u_3 \vec{a}_z$ be a unit vector ^{متجه الوحدة} in the given direction. In figure, we start at (x_0, y_0, z_0) and go a distance s in the direction $\vec{u}$ to the point (x, y, z) ; the vector joining

these points is $s\vec{u}$. Then, $(x, y, z) - (x_0, y_0, z_0) = s\vec{u} = s(u_1, u_2, u_3)$ or $\begin{cases} x = x_0 + u_1 s \\ y = y_0 + u_2 s \\ z = z_0 + u_3 s \end{cases}$



$$\frac{df}{ds} = \vec{\nabla} f \cdot \vec{u}$$

where

$$\vec{\nabla} f \equiv \frac{\partial f}{\partial x} \vec{a}_x + \frac{\partial f}{\partial y} \vec{a}_y + \frac{\partial f}{\partial z} \vec{a}_z \quad \checkmark$$

and

متجه الوحدة (طول 1)
يعبر فقط عن الاتجاه

$\frac{df}{ds}$ = directional derivative

in Cartesian system

$$\boxed{\nabla f \cdot \vec{u}} = |\nabla f| \cos \theta$$

المتجه = متجه الوحدة = $\vec{u}$
مقدار

$$\vec{u} = \frac{\vec{r}(x, y, z) - \vec{r}(x_0, y_0, z_0)}{|\vec{r}(x, y, z) - \vec{r}(x_0, y_0, z_0)|} = \frac{\Delta \vec{r}}{|\Delta \vec{r}|}$$

$$r = 3a_x + 4a_y$$

$$\hat{u} = \frac{3a_x + 4a_y}{5}$$

When (x, y, z) approaches (x_0, y_0, z_0) then $\vec{u} = \frac{d\vec{r}}{|d\vec{r}|} = \frac{d\vec{r}}{ds}$

$$\frac{df}{ds} = \vec{\nabla} f \cdot \vec{u} = \vec{\nabla} f \cdot \frac{d\vec{r}}{ds}$$

$\frac{df}{ds} = \vec{\nabla} f \cdot \vec{u}$ is the directional derivative (ds is an element of distance in the direction $\vec{u}$)

$$\frac{df}{ds} = |\vec{\nabla} f| |\vec{u}| \cos \theta = |\vec{\nabla} f| \cos \theta, \text{ where } \theta \text{ is the angle between } \vec{u} \text{ and } \vec{\nabla} f.$$

Thus $\frac{df}{ds}$ is the projection of $\vec{\nabla} f$ on direction $\vec{u}$ (see the left figure below). We find the

largest value of $\frac{df}{ds}$ (namely $|\vec{\nabla} f|$) if we go in the direction of $\vec{\nabla} f$ ($\theta=0$.)

$$\left(\frac{df}{ds} \right)_{\max} = |\vec{\nabla} f|$$

$$\theta = 0$$

$$\cos \theta = 1$$

$$\frac{df}{ds} = |\nabla f|$$

$$ds_{\max}$$

The gradient of a scalar field $f(x, y, z)$ is a vector field $\vec{\nabla} f$ that points in the direction of the greatest rate of increase of the scalar field, and whose magnitude is that rate of increase.

EXAMPLE 3.4

Given $W = x^2y^2 + xyz$, compute ∇W and the direction derivative dW/dl in the direction $3\mathbf{a}_x + 4\mathbf{a}_y + 12\mathbf{a}_z$ at $(2, -1, 0)$.

Solution:

$$\begin{aligned}\nabla W &= \frac{\partial W}{\partial x} \mathbf{a}_x + \frac{\partial W}{\partial y} \mathbf{a}_y + \frac{\partial W}{\partial z} \mathbf{a}_z \\ &= (2xy^2 + yz)\mathbf{a}_x + (2x^2y + xz)\mathbf{a}_y + (xy)\mathbf{a}_z\end{aligned}$$

At $(2, -1, 0)$: $\nabla W = 4\mathbf{a}_x - 8\mathbf{a}_y - 2\mathbf{a}_z$ •

Hence,

$$\frac{dW}{dl} = \nabla W \cdot \mathbf{a}_l = (4, -8, -2) \cdot \frac{(3, 4, 12)}{13} = -\frac{44}{13}$$

Directional derivative = $\frac{df}{ds}$

rate of change of f with distance s

$$\frac{df}{ds} = \nabla f \cdot \hat{u} = |\nabla f| \cos \theta$$

$$\nabla f = \frac{\partial f}{\partial x} \hat{a}_x + \frac{\partial f}{\partial y} \hat{a}_y + \frac{\partial f}{\partial z} \hat{a}_z$$

$$\hat{u} = \frac{\Delta r}{|\Delta r|}$$

$\theta = 0$ اى معدل التغير عندما تكون

$$\frac{df}{ds} = |\nabla f|$$

وهو نفس مقياس ∇f

EXAMPLE 3.4

Given $W = x^2y^2 + xyz$, compute ∇W and the direction derivative dW/dl in the direction $3\hat{a}_x + 4\hat{a}_y + 12\hat{a}_z$ at $(2, -1, 0)$.

a)

$$\nabla W = \frac{\partial W}{\partial x} \hat{a}_x + \frac{\partial W}{\partial y} \hat{a}_y + \frac{\partial W}{\partial z} \hat{a}_z$$

$$\nabla W = (2xy^2 + yz) \hat{a}_x + (2yx^2 + xz) \hat{a}_y + (xy) \hat{a}_z$$

$$\nabla W = (2(-1)(-1) + 0) \hat{a}_x + (2(-1)(4) + 0) \hat{a}_y + ((2)(-1)) \hat{a}_z$$

$$\nabla W = -4\hat{a}_x - 8\hat{a}_y - 2\hat{a}_z$$

b)

$$\frac{dW}{dl} = \nabla W \cdot \hat{u}$$

$$\hat{u} = \frac{\vec{l}}{|\vec{l}|} = \frac{3\hat{a}_x + 4\hat{a}_y + 12\hat{a}_z}{\sqrt{3^2 + 4^2 + 12^2}}$$

$$\hat{u} = \frac{1}{13} (3\hat{a}_x + 4\hat{a}_y + 12\hat{a}_z)$$

$$\frac{dW}{dl} = \nabla W \cdot \hat{u} = \frac{1}{13} (-4\hat{a}_x - 8\hat{a}_y - 2\hat{a}_z) \cdot (3\hat{a}_x + 4\hat{a}_y + 12\hat{a}_z) = \frac{-44}{13}$$

5- Divergence of a vector and divergence theorem

The divergence of a vector field $\vec{A}$ at a given point P is the net outward flux over a closed surface S per unit volume as the volume shrinks about P .




$$\text{div} \vec{A} = \vec{\nabla} \cdot \vec{A} \equiv \lim_{\Delta v \rightarrow 0} \frac{\oint_S \vec{A} \cdot d\vec{S}}{\Delta v}$$

$$\text{div} A = \nabla \cdot \vec{A} = \lim_{\Delta v \rightarrow 0} \frac{\oint A \cdot dS}{\Delta v}$$

where Δv is the volume enclosed by the closed surface S in which P is located.

-The physical significance of the divergence of a vector field

The divergence of the vector field $\vec{A}$ at a point P is a measure of how much the field diverges or spreads out from that point.



$\text{div} = \text{zero}$

$\text{div} f \Rightarrow \text{واحد في}$

Figure. Illustration of the divergence of a vector field at P ; (a) positive divergence, (b) negative divergence, (c) zero divergence.

The divergence of $\vec{A}$ at point $P(x_0, y_0, z_0)$ in Cartesian system is given by

الكارتيثية
 $\nabla \cdot \vec{A}$

$$\vec{\nabla} \cdot \vec{A} = \frac{\partial A_x}{\partial x} + \frac{\partial A_y}{\partial y} + \frac{\partial A_z}{\partial z}$$

$$f = 2x + y + z$$

$$\nabla \cdot f = 2 + 1 + 1 = 4$$

$$f = 2x a_x + y a_y + 3z a_z$$

$$\nabla \cdot f = 2 + 1 + 3 = 6$$

The divergence of $\vec{A}$ at point $P(x_0, y_0, z_0)$ in cylindrical coordinates

الاسطوانية
 $\nabla \cdot \vec{A}$

$$\vec{\nabla} \cdot \vec{A} = \frac{1}{\rho} \frac{\partial}{\partial \rho} (\rho A_\rho) + \frac{1}{\rho} \frac{\partial A_\phi}{\partial \phi} + \frac{\partial A_z}{\partial z}$$



The divergence of $\vec{A}$ at point $P(x_0, y_0, z_0)$ in spherical coordinates

الكرية
 $\nabla \cdot \vec{A}$

$$\vec{\nabla} \cdot \vec{A} = \frac{1}{r^2} \frac{\partial}{\partial r} (r^2 A_r) + \frac{1}{r \sin \theta} \frac{\partial}{\partial \theta} (A_\theta \sin \theta) + \frac{1}{r \sin \theta} \frac{\partial A_\phi}{\partial \phi}$$



- Properties of the divergence of a vector field:

- 1- $\nabla \cdot \vec{A}$ is a scalar field. قياسية
- 2- The divergence of a scalar field $\underline{V}$, $\nabla \cdot \underline{V}$, makes no sense ليس له معنى
- 3- $\nabla \cdot (\vec{A} + \vec{B}) = \nabla \cdot \vec{A} + \nabla \cdot \vec{B}$ - يجوز التوزيع
- 4- $\nabla \cdot (V \vec{A}) = V \nabla \cdot \vec{A} + \vec{A} \cdot \nabla V$ د.ف. لـ مقياسية

EXAMPLE 3.6

Determine the divergence of these vector fields:

(a) $\mathbf{P} = x^2 yz \mathbf{a}_x + xz \mathbf{a}_z$

(b) $\mathbf{Q} = \rho \sin \phi \mathbf{a}_\rho + \rho^2 z \mathbf{a}_\phi + z \cos \phi \mathbf{a}_z$

Solution:

$$\begin{aligned} \text{(a) } \nabla \cdot \mathbf{P} &= \frac{\partial}{\partial x} P_x + \frac{\partial}{\partial y} P_y + \frac{\partial}{\partial z} P_z \\ &= \frac{\partial}{\partial x} (x^2 yz) + \frac{\partial}{\partial y} (0) + \frac{\partial}{\partial z} (xz) \\ &= \underline{2xyz} + x \end{aligned}$$

$$\begin{aligned} \text{(b) } \nabla \cdot \mathbf{Q} &= \frac{1}{\rho} \frac{\partial}{\partial \rho} (\rho Q_\rho) + \frac{1}{\rho} \frac{\partial}{\partial \phi} Q_\phi + \frac{\partial}{\partial z} Q_z \\ &= \frac{1}{\rho} \frac{\partial}{\partial \rho} (\rho^2 \sin \phi) + \frac{1}{\rho} \frac{\partial}{\partial \phi} (\rho^2 z) + \frac{\partial}{\partial z} (z \cos \phi) \\ &= 2 \sin \phi + \cos \phi \end{aligned}$$

$$\begin{aligned} \text{a) } \nabla \cdot \mathbf{P} &= \frac{\partial P_x}{\partial x} + \frac{\partial P_y}{\partial y} + \frac{\partial P_z}{\partial z} \\ &= 2xyz + 0 + x \end{aligned}$$

$$\boxed{\nabla \cdot \mathbf{P} = 2xyz + x}$$

$$\nabla \cdot \mathbf{Q} = \frac{1}{\rho} \frac{\partial \rho Q_\rho}{\partial \rho} + \frac{1}{\rho} \frac{\partial Q_\phi}{\partial \phi} + \frac{\partial Q_z}{\partial z}$$

$$\nabla \cdot \mathbf{Q} = \frac{1}{\rho} \frac{\partial}{\partial \rho} \rho^2 \sin \phi + \frac{1}{\rho} \frac{\partial}{\partial \phi} (\rho^2 z) + \frac{\partial}{\partial z} (z \cos \phi) = 2 \sin \phi + 0 + \cos \phi$$

- Divergence theorem:

$$\oint \vec{A} \cdot d\vec{S} = \int_V \nabla \cdot \vec{A} dv$$



From the definition of the divergence of $\vec{A}$, it is not difficult to expect that

$$\oint_S \vec{A} \cdot d\vec{S} = \int_V (\nabla \cdot \vec{A}) dv$$

divergence theorem

The divergence theorem states that the **total outward flux of a vector field $\vec{A}$ through the closed surface S is the same as the volume integral of the divergence of $\vec{A}$**

$$\vec{G} = 10e^{-2z} \vec{a}_\rho + 10e^{-2z} \vec{a}_z$$

$$\oint \vec{G} \cdot d\vec{S}$$

EXAMPLE 3.7

If $\vec{G}(r) = 10e^{-2z}(\rho \vec{a}_\rho + \vec{a}_z)$, determine the flux of $\vec{G}$ out of the entire surface of the cylinder
 $\rho = 1, 0 \leq z \leq 1$. Confirm the result using the divergence theorem.

Solution:

$$\oint \vec{G} \cdot d\vec{S} = \int_V \nabla \cdot \vec{G} dv$$

$$\Psi = \oint_S \vec{G} \cdot d\vec{S} = \int_V (\nabla \cdot \vec{G}) dv$$

$$\begin{aligned} \nabla \cdot \vec{G} &= \frac{1}{\rho} \frac{\partial}{\partial \rho} \rho G_\rho + \frac{1}{\rho} \frac{\partial}{\partial \phi} G_\phi + \frac{\partial}{\partial z} G_z \\ \nabla \cdot \vec{G} &= \frac{1}{\rho} \frac{\partial}{\partial \rho} 10e^{-2z} \rho^2 + \frac{\partial}{\partial z} 10e^{-2z} \\ &= \frac{1}{\rho} \frac{\partial}{\partial \rho} (20e^{-2z} \rho) + \frac{\partial}{\partial z} 10e^{-2z} \\ &= 2e^{-2z} - 20e^{-2z} = -18e^{-2z} \end{aligned}$$

$$\begin{aligned} \int \nabla \cdot \vec{G} dv &= \int 0 dv \\ &= 0 \end{aligned}$$

$$\nabla \cdot \vec{G} = 20e^{-2z} + 0 - 20e^{-2z} = 0 \quad \Psi = \int_V (\nabla \cdot \vec{G}) dv = 0$$

6- Curl of a vector and Stokes's theorem

$$\nabla \times \vec{A}$$



The curl of $\vec{A}$ ($\text{curl } \vec{A}$ or $\vec{\nabla} \times \vec{A}$) is a vector whose magnitude is the maximum circulation of $\vec{A}$ per unit area as the area tends to zero and whose direction is the normal direction of the area when the area is oriented so as to make the circulation maximum.

$$\text{curl } \vec{A} = \vec{\nabla} \times \vec{A} \equiv \left(\lim_{\Delta S \rightarrow 0} \frac{\oint_L \vec{A} \cdot d\vec{l}}{\Delta S} \right)_{\text{max}} \vec{a}_n$$

Curle

$$\nabla \times \vec{A} = \left(\lim_{\Delta S \rightarrow 0} \frac{\oint \vec{A} \cdot d\vec{l}}{\Delta S} \right)_{\text{max}} \hat{a}_n$$

ΔS : area bounded by the closed path L

$\vec{a}_n$: unit vector normal to the surface ΔS and is determined using the right-hand rule.

-The physical significance of the curl of a vector field

1- The curl provides the maximum value of the circulation of the field per unit area (or circulation density) and indicates the direction along which this maximum value occurs.

2- The curl of a vector field $\vec{A}$ at a point P may be regarded as a measure of the circulation or how much the field curls around P.

In Cartesian coordinates $\vec{\nabla} \times \vec{A}$ is found using

$$\vec{\nabla} \times \vec{A} = \begin{vmatrix} \vec{a}_x & \vec{a}_y & \vec{a}_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ A_x & A_y & A_z \end{vmatrix}$$

or

$$\vec{\nabla} \times \vec{A} = \left[\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right] \vec{a}_x - \left[\frac{\partial A_z}{\partial x} - \frac{\partial A_x}{\partial z} \right] \vec{a}_y + \left[\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right] \vec{a}_z$$

We obtain $\vec{\nabla} \times \vec{A}$ in cylindrical coordinates as

$$\vec{\nabla} \times \vec{A} = \frac{1}{\rho} \begin{vmatrix} \vec{a}_\rho & \rho \vec{a}_\phi & \vec{a}_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ A_\rho & \rho A_\phi & A_z \end{vmatrix}$$

$$\frac{1}{\rho} \begin{vmatrix} a_\rho & \rho a_\phi & a_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ A_\rho & \rho A_\phi & A_z \end{vmatrix}$$

or

$$\vec{\nabla} \times \vec{A} = \left[\frac{1}{\rho} \frac{\partial A_z}{\partial \phi} - \frac{\partial A_\phi}{\partial z} \right] \vec{a}_\rho - \left[\frac{\partial A_z}{\partial \rho} - \frac{\partial A_\rho}{\partial z} \right] \vec{a}_\phi + \frac{1}{\rho} \left[\frac{\partial(\rho A_\phi)}{\partial \rho} - \frac{\partial A_\rho}{\partial \phi} \right] \vec{a}_z$$

and in spherical coordinates as

$$\vec{\nabla} \times \vec{A} = \frac{1}{r^2 \sin \theta} \begin{vmatrix} \vec{a}_r & r \vec{a}_\theta & r \sin \theta \vec{a}_\phi \\ \frac{\partial}{\partial r} & \frac{\partial}{\partial \theta} & \frac{\partial}{\partial \phi} \\ A_r & r A_\theta & r \sin \theta A_\phi \end{vmatrix}$$

$$\frac{1}{r^2 \sin \theta} \left[\frac{\partial}{\partial \theta} (r \sin \theta A_\phi) - \frac{\partial}{\partial \phi} (r A_\theta) \right] \vec{a}_r$$

or

$$\vec{\nabla} \times \vec{A} = \frac{1}{r \sin \theta} \left[\frac{1}{\rho} \frac{\partial(A_\phi \sin \theta)}{\partial \theta} - \frac{\partial A_\theta}{\partial \phi} \right] \vec{a}_r - \frac{1}{r} \left[\frac{\partial(r A_\phi)}{\partial r} - \frac{1}{\sin \theta} \frac{\partial A_r}{\partial \phi} \right] \vec{a}_\theta + \frac{1}{r} \left[\frac{\partial(r A_\theta)}{\partial r} - \frac{\partial A_r}{\partial \theta} \right] \vec{a}_\phi$$

Properties of the curl of a vector field:

خصائص الدوران

1- The curl of a vector field is another vector field.

النتيجة هي متجه

2- The curl of a scalar field V , $\vec{\nabla} \times V$, makes no sense.

الدوران لأي كمية قياسية ليس له معنى

$$3- \vec{\nabla} \times (\vec{A} + \vec{B}) = \vec{\nabla} \times \vec{A} + \vec{\nabla} \times \vec{B}$$


$$\begin{matrix} a & b & c \\ bac & - cab & + cab & - bac \end{matrix}$$

$$4- \vec{\nabla} \times (\vec{A} \times \vec{B}) = \vec{A}(\vec{\nabla} \cdot \vec{B}) - \vec{B}(\vec{\nabla} \cdot \vec{A}) + (\vec{B} \cdot \vec{\nabla})\vec{A} - (\vec{A} \cdot \vec{\nabla})\vec{B} \quad \checkmark$$

$$5- \vec{\nabla} \times (V\vec{A}) = V\vec{\nabla} \times \vec{A} + \vec{\nabla} V \times \vec{A} \quad \checkmark$$

6- The divergence of the curl of a vector field vanishes, that is, $\vec{\nabla} \cdot (\vec{\nabla} \times \vec{A}) = 0$.

7- The curl of the gradient of a scalar vanishes, that is, $\vec{\nabla} \times \vec{\nabla} V = 0$



curl = zero


خارج الورق

$$\vec{v}_a = -y\hat{x} + x\hat{y}$$



$$(1,0) \quad v_a = \hat{y}$$

$$(0,1) \quad v_a = -\hat{x}$$

$$(-1,0) \quad v_a = -\hat{y}$$



$$\vec{v}_a = -y\hat{x} + x\hat{y}$$



$$\nabla \times \vec{v} = \begin{vmatrix} a_x & a_y & a_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ -y & x & 0 \end{vmatrix}$$

$$a_x \begin{vmatrix} \frac{\partial}{\partial x} & \frac{\partial}{\partial z} \\ x & 0 \end{vmatrix} - a_y \begin{vmatrix} \frac{\partial}{\partial x} & \frac{\partial}{\partial z} \\ -y & 0 \end{vmatrix} + a_z \begin{vmatrix} \frac{\partial}{\partial x} & \frac{\partial}{\partial y} \\ -y & x \end{vmatrix}$$

$$a_x \left(\frac{\partial}{\partial x} 0 - \frac{\partial}{\partial z} x \right) - a_y \left(\frac{\partial}{\partial x} 0 - \frac{\partial}{\partial z} (-y) \right) + a_z \left(\frac{\partial}{\partial x} x - \frac{\partial}{\partial y} (-y) \right)$$

$$(0 - 0)a_x - (0 - 0)a_y + (1 - -1)a_z = 2a_z$$

EXAMPLE 3.8

Determine the curl of the vector fields in Example 3.6.

Solution:

$$\begin{aligned} \text{(a) } \nabla \times \mathbf{P} &= \left(\frac{\partial P_z}{\partial y} - \frac{\partial P_y}{\partial z} \right) \mathbf{a}_x + \left(\frac{\partial P_x}{\partial z} - \frac{\partial P_z}{\partial x} \right) \mathbf{a}_y + \left(\frac{\partial P_y}{\partial x} - \frac{\partial P_x}{\partial y} \right) \mathbf{a}_z \\ &= (0 - 0) \mathbf{a}_x + (x^2 y - z) \mathbf{a}_y + (0 - x^2 z) \mathbf{a}_z \\ &= (x^2 y - z) \mathbf{a}_y - x^2 z \mathbf{a}_z \end{aligned}$$

$$\begin{aligned} \text{(b) } \nabla \times \mathbf{Q} &= \left[\frac{1}{\rho} \frac{\partial Q_z}{\partial \phi} - \frac{\partial Q_\phi}{\partial z} \right] \mathbf{a}_\rho + \left[\frac{\partial Q_\rho}{\partial z} - \frac{\partial Q_z}{\partial \rho} \right] \mathbf{a}_\phi + \frac{1}{\rho} \left[\frac{\partial}{\partial \rho} (\rho Q_\phi) - \frac{\partial Q_\rho}{\partial \phi} \right] \mathbf{a}_z \\ &= \left(\frac{-z}{\rho} \sin \phi - \rho^2 \right) \mathbf{a}_\rho + (0 - 0) \mathbf{a}_\phi + \frac{1}{\rho} (3\rho^2 z - \rho \cos \phi) \mathbf{a}_z \\ &= -\frac{1}{\rho} (z \sin \phi + \rho^3) \mathbf{a}_\rho + (3\rho z - \cos \phi) \mathbf{a}_z \end{aligned}$$

EXAMPLE 3.6

Determine the ~~divergence~~ ^{curl} of these vector fields:

(a) $\mathbf{P} = x^2 y z \mathbf{a}_x + x z \mathbf{a}_z$

(b) $\mathbf{Q} = \underbrace{\rho \sin \phi}_{A_\rho} \mathbf{a}_\rho + \underbrace{\rho^2 z}_{A_\phi} \mathbf{a}_\phi + \underbrace{z \cos \phi}_{A_z} \mathbf{a}_z$

$$\nabla \times \mathbf{P} = \begin{vmatrix} \mathbf{a}_x & \mathbf{a}_y & \mathbf{a}_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ x^2 y z & 0 & x z \end{vmatrix}$$

$$= \left[\frac{\partial}{\partial y} x z - \frac{\partial}{\partial z} 0 \right] \hat{\mathbf{a}}_x - \left[\frac{\partial}{\partial x} x z - \frac{\partial}{\partial z} x^2 y z \right] \hat{\mathbf{a}}_y + \left[\frac{\partial}{\partial x} 0 - \frac{\partial}{\partial y} x^2 y z \right] \mathbf{a}_z$$

$$0 \hat{\mathbf{a}}_x - [z - x^2 y] \mathbf{a}_y + [x^2 z] \mathbf{a}_z$$

$$\nabla \times \mathbf{P} = [x^2 y - z] \mathbf{a}_y + x^2 z \mathbf{a}_z$$

$$\nabla \times \mathbf{Q} = \frac{1}{\rho} \begin{vmatrix} \mathbf{a}_\rho & \rho \mathbf{a}_\phi & \mathbf{a}_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ A_\rho & \rho A_\phi & A_z \end{vmatrix} = \frac{1}{\rho} \begin{vmatrix} \hat{\mathbf{a}}_\rho & \rho \hat{\mathbf{a}}_\phi & \hat{\mathbf{a}}_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ \rho \sin \phi & \rho^2 z & z \cos \phi \end{vmatrix}$$

$$\frac{1}{\rho} \left[\frac{\partial}{\partial \phi} z \cos \phi - \frac{\partial}{\partial z} \rho^2 z \right] \mathbf{a}_\rho - \frac{1}{\rho} \left[\frac{\partial}{\partial \rho} z \cos \phi - \frac{\partial}{\partial z} \rho \sin \phi \right] \mathbf{a}_\phi$$

$$+ \frac{1}{\rho} \left[\frac{\partial}{\partial \rho} \rho^2 z - \frac{\partial}{\partial \phi} \rho \sin \phi \right] \mathbf{a}_z$$


$$\frac{1}{\rho} [z \sin \phi - \rho^2] \mathbf{a}_\rho - \frac{1}{\rho} [0 - 0] \mathbf{a}_\phi + \frac{1}{\rho} [3 \rho^2 z - \rho \cos \phi] \mathbf{a}_z$$

$$-\frac{1}{\rho} [z \sin \phi - \rho^2] \mathbf{a}_\rho + [3 \rho z - \cos \phi] \mathbf{a}_z$$

-Stokes's theorem

From the definition of the curl of $\vec{A}$, we may expect that

$$\oint_L \vec{A} \cdot d\vec{l} = \int_S (\vec{\nabla} \times \vec{A}) \cdot \vec{a}_n dS$$



Stokes's theorem

Stokes's theorem states that the **circulation** of a vector field $\vec{A}$ around a **closed path L** is **equal to the surface integral** of $\vec{\nabla} \times \vec{A}$ over the **open surface S** bounded by L provided that $\vec{A}$ and $\vec{\nabla} \times \vec{A}$ are continuous on S.

$$\oint \vec{A} \cdot d\vec{l} = \int (\nabla \times \vec{A}) \cdot \vec{a}_n dS$$




Figure. Determining the sense of $d\vec{l}$ and $d\vec{S}$ involved in Stokes's Theorem

PRACTICE EXERCISE 3.9

Use Stokes's theorem to confirm your result in Practice Exercise 3.2.

Answer: 1.

PRACTICE EXERCISE 3.2

Calculate the circulation of


$$\mathbf{A} = \rho \cos \phi \mathbf{a}_\rho + z \sin \phi \mathbf{a}_z$$

around the edge L of the wedge defined by $0 \leq \rho \leq 2$, $0 \leq \phi \leq 60^\circ$, $z = 0$ and shown in Figure 3.11.

Answer: 1.

$$\oint \mathbf{A} \cdot d\mathbf{L} = \int_S \nabla \times \mathbf{A} \cdot d\mathbf{s}$$

عينة من سؤالات باستخدام التفاضل



$$\nabla \times \mathbf{A} = \frac{1}{\rho} \begin{vmatrix} \hat{\mathbf{a}}_\rho & \rho \hat{\mathbf{a}}_\phi & \hat{\mathbf{a}}_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ \rho \cos \phi & \rho(0) & z \sin \phi \end{vmatrix}$$

$$\nabla \times \mathbf{A} = \frac{1}{\rho} [z \cos \phi - 0] \hat{\mathbf{a}}_\rho - \frac{1}{\rho} [0 - 0] \rho \hat{\mathbf{a}}_\phi$$

$$\frac{1}{\rho} [0 - -\rho \sin \phi] \mathbf{a}_z$$

$$\nabla \times \mathbf{A} = \frac{1}{\rho} [z \cos \phi \mathbf{a}_\rho] + [\sin \phi \mathbf{a}_z]$$

$$\oint (\nabla \times \mathbf{A}) \cdot d\mathbf{s} = \int_S \left[\frac{z \cos \phi}{\rho} \hat{\mathbf{a}}_\rho + \sin \phi \mathbf{a}_z \right] \cdot [\rho d\rho d\phi \hat{\mathbf{a}}_z]$$

Zero

$\mathbf{a}_z \cdot \mathbf{a}_z = 1$

$$\int (\nabla \times A) \cdot d\mathbf{S} = \int_0^5 \int_0^{60} \rho \sin \phi \, d\rho \, d\phi$$

$$= \int_0^2 \rho \, d\rho \int_0^{60} \sin \phi \, d\phi$$

$$= \left[\frac{\rho^2}{2} \right]_0^2 \left[-\cos \phi \right]_0^{60}$$

$$\left(\frac{4-0}{2} \right) (-\cos 60 - \cos 0)$$

$$2 \left(-\frac{1}{2} + 1 \right)$$

$$2 \left(\frac{1}{2} \right) = 1$$

EXAMPLE 3.9

If $\mathbf{A} = \rho \cos \phi \mathbf{a}_\rho + \sin \phi \mathbf{a}_\phi$, evaluate $\oint \mathbf{A} \cdot d\mathbf{l}$ around the path shown in Figure 3.22. Confirm this using Stokes's theorem.

Solution:

Using Stokes's theorem (because L is a closed path)


$$\oint_L \mathbf{A} \cdot d\mathbf{l} = \int_S (\nabla \times \mathbf{A}) \cdot d\mathbf{S}$$

But $d\mathbf{S} = \rho d\phi d\rho \mathbf{a}_z$ and

$$\begin{aligned} \nabla \times \mathbf{A} &= \mathbf{a}_\rho \left[\frac{1}{\rho} \frac{\partial A_z}{\partial \phi} - \frac{\partial A_\phi}{\partial z} \right] + \mathbf{a}_\phi \left[\frac{\partial A_\rho}{\partial z} - \frac{\partial A_z}{\partial \rho} \right] + \mathbf{a}_z \frac{1}{\rho} \left[\frac{\partial}{\partial \rho} (\rho A_\phi) - \frac{\partial A_\rho}{\partial \phi} \right] \\ &= (0 - 0)\mathbf{a}_\rho + (0 - 0)\mathbf{a}_\phi + \frac{1}{\rho} (1 + \rho) \sin \phi \mathbf{a}_z \end{aligned}$$

Hence:

$$\begin{aligned} \int_S (\nabla \times \mathbf{A}) \cdot d\mathbf{S} &= \int_{\phi=30^\circ}^{60^\circ} \int_{\rho=2}^5 \frac{1}{\rho} (1 + \rho) \sin \phi \rho d\rho d\phi \\ &= \int_{30^\circ}^{60^\circ} \sin \phi d\phi \int_2^5 (1 + \rho) d\rho \\ &= -\cos \phi \Big|_{30^\circ}^{60^\circ} \left(\rho + \frac{\rho^2}{2} \right) \Big|_2^5 \\ &= \frac{27}{4} (\sqrt{3} - 1) = 4.941 \end{aligned}$$



EXAMPLE 3.9

If $\mathbf{A} = \rho \cos \phi \mathbf{a}_\rho + \sin \phi \mathbf{a}_\phi$, evaluate $\oint \mathbf{A} \cdot d\mathbf{l}$ around the path shown in Figure 3.22. Confirm this using Stokes's theorem.

Solution:

Let

$$\oint_L \mathbf{A} \cdot d\mathbf{l} = \underbrace{\left[\int_a^b + \int_b^c + \int_c^d + \int_d^a \right] \mathbf{A} \cdot d\mathbf{l}}$$




Figure 3.22 For Example 3.9.

where path L has been divided into segments ab , bc , cd , and da as in Figure 3.22.

Along ab , $\rho = 2$ and $d\mathbf{l} = \rho d\phi \mathbf{a}_\phi$. Hence,

$$\int_a^b \mathbf{A} \cdot d\mathbf{l} = \int_{\phi=60^\circ}^{30^\circ} \rho \sin \phi d\phi = 2(-\cos \phi) \Big|_{60^\circ}^{30^\circ} = -(\sqrt{3} - 1)$$

Along bc , $\phi = 30^\circ$ and $d\mathbf{l} = d\rho \mathbf{a}_\rho$. Hence,

$$\int_b^c \mathbf{A} \cdot d\mathbf{l} = \int_{\rho=2}^5 \rho \cos \phi d\rho = \cos 30^\circ \frac{\rho^2}{2} \Big|_2^5 = \frac{21\sqrt{3}}{4}$$

Along cd , $\rho = 5$ and $d\mathbf{l} = \rho d\phi \mathbf{a}_\phi$. Hence,

$$\int_c^d \mathbf{A} \cdot d\mathbf{l} = \int_{\phi=30^\circ}^{60^\circ} \rho \sin \phi d\phi = 5(-\cos \phi) \Big|_{30^\circ}^{60^\circ} = \frac{5}{2}(\sqrt{3} - 1)$$

Along da , $\phi = 60^\circ$ and $d\mathbf{l} = d\rho \mathbf{a}_\rho$. Hence,

$$\int_d^a \mathbf{A} \cdot d\mathbf{l} = \int_{\rho=5}^2 \rho \cos \phi d\rho = \cos 60^\circ \frac{\rho^2}{2} \Big|_5^2 = -\frac{21}{4}$$

Putting all these together results in

$$\begin{aligned} \oint_L \mathbf{A} \cdot d\mathbf{l} &= -\sqrt{3} + 1 + \frac{21\sqrt{3}}{4} + \frac{5\sqrt{3}}{2} - \frac{5}{2} - \frac{21}{4} \\ &= \frac{27}{4}(\sqrt{3} - 1) = 4.941 \end{aligned}$$


EXAMPLE 3.9

If $\mathbf{A} = \rho \cos \phi \mathbf{a}_\rho + \sin \phi \mathbf{a}_\phi$, evaluate $\oint \mathbf{A} \cdot d\mathbf{l}$ around the path shown in Figure 3.22. Confirm this using Stokes's theorem.

$$\oint \mathbf{A} \cdot d\mathbf{l} = \int (\nabla \times \mathbf{A}) \cdot d\mathbf{s}$$

$$d\mathbf{s} = \rho d\phi d\rho \mathbf{a}_z$$

$$\nabla \times \mathbf{A} = \frac{1}{\rho} \begin{vmatrix} \hat{\mathbf{a}}_\rho & \rho \hat{\mathbf{a}}_\phi & \mathbf{a}_z \\ \frac{\partial}{\partial \rho} & \frac{\partial}{\partial \phi} & \frac{\partial}{\partial z} \\ \rho \cos \phi & \rho \sin \phi & 0 \end{vmatrix}$$



$$\frac{1}{\rho} [0 - 0] \hat{\mathbf{a}}_\rho - \frac{1}{\rho} [0 - 0] \mathbf{a}_\phi + \frac{1}{\rho} [\sin \phi + \rho \sin \phi] \mathbf{a}_z$$

$$\nabla \times \mathbf{A} = \frac{1}{\rho} (1 + \rho) \sin \phi \mathbf{a}_z$$

$$\int (\nabla \times \mathbf{A}) \cdot d\mathbf{s} =$$

$$\hat{\mathbf{a}}_z \cdot \hat{\mathbf{a}}_z = 1$$

$$\int \left(\frac{1}{\rho} (1 + \rho) \sin \phi \hat{\mathbf{a}}_z \right) \cdot (\rho d\rho d\phi \hat{\mathbf{a}}_z)$$

$$\int \sin \phi (1 + \rho) d\rho d\phi$$

$$= \int_{30}^{60} \sin \phi \, d\phi \int_2^5 (1+\rho) \, d\rho$$

$$= \left(-\cos \phi \right)_{30}^{60} \left(\rho + \frac{\rho^2}{2} \right)_2^5$$

$$[-\cos 60 + \cos 30] \left[\left(5 + \frac{25}{2} \right) - \left(2 + \frac{4}{2} \right) \right]$$

$$= 4.941$$

①

طريقة 2

$$\int A \cdot d\mathbf{l} = \int_a^b A \cdot d\mathbf{l} + \int_b^c A \cdot d\mathbf{l} + \int_c^d A \cdot d\mathbf{l} + \int_d^a A \cdot d\mathbf{l}$$

① $\int_a^b A \cdot d\mathbf{l} = \int_a^b (\rho \cos \phi \hat{a}_\rho + \sin \phi \hat{a}_\phi) \cdot (\rho \, d\phi \hat{a}_\phi)$

$\hat{a}_\rho \cdot \hat{a}_\phi = 0$
 $\hat{a}_\phi \cdot \hat{a}_\phi = 1$

$$\int_{60}^{30} \rho \sin \phi \, d\phi = \rho \int_{60}^{30} \sin \phi \, d\phi$$

$$\rho \left[-\cos \phi \right]_{60}^{30} = -2 [\cos 30 - \cos 60]$$

$$= 1 - \sqrt{3}$$

② $\int_b^f A \cdot d\mathbf{l} \quad \phi = 30 \quad d\mathbf{l} = \rho \, d\rho \hat{a}_\rho$

$$\int (p \cos \phi \hat{a}_\phi) \cdot (dp \hat{a}_\phi) = \int p \cos \phi dp$$

$$\cos 30 \int_2^5 p dp = \cos 30 \left[\frac{p^2}{2} \right]_2^5$$

$$= \cos 30 \left[\frac{25}{2} - \frac{4}{2} \right] = \frac{21\sqrt{3}}{4}$$

③ $\int A \cdot dl$ $p=5$ $dl = p d\phi \hat{a}_\phi$

$$\int_0^c (5 \sin \phi \hat{a}_\phi) \cdot (p d\phi \hat{a}_\phi) = \int p \sin \phi d\phi$$

$$5 \int_{30}^{60} \sin \phi d\phi = 5 \left(-\cos \phi \right)_{30}^{60}$$

$$= -5 [\cos 60 - \cos 30] = \frac{5}{3}(\sqrt{3} - 1)$$

④ $\int A \cdot dl$ $\phi = 60$ $dl = dp \hat{a}_p$

$$\int (p \cos \phi \hat{a}_\phi) \cdot (dp \hat{a}_p) = \cos 60 \int_5^2 p dp$$

$$= \cos 60 \left[\frac{p^2}{2} \right]_5^2 = \cos 60 \left[\frac{4}{2} - \frac{25}{2} \right] = -\frac{21}{4}$$

$$\oint A \cdot dl = \int^{(1)} + \int^{(2)} + \int^{(3)} + \int^{(4)} = 4.941$$

7- Conservative Fields

المحافظ، الحفظ



A vector fields, $\vec{A}$, for which $\int_A^B \vec{A} \cdot d\vec{l}$ depends upon the path from A to B is called nonconservative. There are however, conservative fields for which $\int_A^B \vec{A} \cdot d\vec{l}$ is the same between the two given points regardless of what path we calculate it along.

$\vec{\nabla} \times \vec{A} = \vec{0}$ is a necessary and sufficient condition for $\int_A^B \vec{A} \cdot d\vec{l}$ to be independent of the path, that is, $\vec{\nabla} \times \vec{A} = \vec{0}$ for conservative fields and $\vec{\nabla} \times \vec{A} \neq \vec{0}$ for nonconservative fields.

محافظ $\vec{\nabla} \times \vec{A} = 0$
غير محافظ $\vec{\nabla} \times \vec{A} \neq 0$
لا يصف التخلل الحثضي، بار

components of $\vec{\nabla} \times \vec{A}$ are equal to zero.

$$\boxed{\text{If } \vec{A} = \vec{\nabla} f, \text{ then } \vec{\nabla} \times \vec{A} = \vec{0}}$$

Conversely,

$$\boxed{\text{If } \vec{\nabla} \times \vec{A} = \vec{0}, \text{ then we can find a function } f(x,y,z) \text{ for which } \vec{A} = \vec{\nabla} f}$$

Example: Show that $\vec{A} = (2xy - z^3)\vec{a}_x + x^2\vec{a}_y - (3xz^2 + 1)\vec{a}_z$ is conservative,

Solution:

$$\vec{\nabla} \times \vec{A} = \left[\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right] \vec{a}_x - \left[\frac{\partial A_z}{\partial x} - \frac{\partial A_x}{\partial z} \right] \vec{a}_y + \left[\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right] \vec{a}_z$$

$$\frac{\partial A_z}{\partial y} = \frac{\partial(-3xz^2 - 1)}{\partial y} = 0, \quad \frac{\partial A_y}{\partial z} = \frac{\partial(x^2)}{\partial z} = 0, \quad \frac{\partial A_z}{\partial x} = \frac{\partial(-3xz^2 - 1)}{\partial x} = -3z^2$$

$$\frac{\partial A_x}{\partial z} = \frac{\partial(2xy - z^3)}{\partial z} = -3z^2, \quad \frac{\partial A_y}{\partial x} = \frac{\partial(x^2)}{\partial x} = 2x, \quad \frac{\partial A_x}{\partial y} = \frac{\partial(2xy - z^3)}{\partial y} = 2x$$

$$\vec{\nabla} \times \vec{A} = [0 - 0]\vec{a}_x - [-3z^2 + 3z^2]\vec{a}_y + [2x - 2x]\vec{a}_z = \vec{0} \text{ so } \vec{A} \text{ is conservative}$$

Example: Show that $\vec{A} = \underline{(2xy - z^3)}\vec{a}_x + x^2\vec{a}_y - (3xz^2 + 1)\vec{a}_z$ is conservative,

$$\nabla \times \vec{A} = \begin{vmatrix} \hat{a}_x & \hat{a}_y & \hat{a}_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ 2xy - z^3 & x^2 & -3xz^2 + 1 \end{vmatrix}$$

$$= \left[\frac{\partial}{\partial y}(-3xz^2 + 1) - \frac{\partial}{\partial z}x^2 \right] \hat{a}_x - \left[\frac{\partial}{\partial x}(-3xz^2 + 1) - \frac{\partial}{\partial z}(2xy - z^3) \right] \hat{a}_y$$

$$+ \left[\frac{\partial}{\partial x}x^2 - \frac{\partial}{\partial y}(2xy - z^3) \right] \hat{a}_z$$

$$= 0 \hat{a}_x - [-3z^2 + 3z^2] \hat{a}_y + [2x - 2x] \hat{a}_z$$

$$0 \hat{a}_x - 0 \hat{a}_y + 0 \hat{a}_z$$

$$= 0$$

$\vec{A}$ is conservative


(a) $\nabla \cdot \mathbf{A} = 0, \nabla \times \mathbf{A} = 0$

(b) $\nabla \cdot \mathbf{A} \neq 0, \nabla \times \mathbf{A} = 0$


(c) $\nabla \cdot \mathbf{A} = 0, \nabla \times \mathbf{A} \neq 0$

(d) $\nabla \cdot \mathbf{A} \neq 0, \nabla \times \mathbf{A} \neq 0$


Figure 3.23 illustrates typical fields in these four categories.




(a)



(b)



(c)



(d)

Laplacian of a scalar $\nabla^2 V$

The Laplacian of a scalar field V , written as $\nabla^2 V$, is the divergence of the gradient of V .

$$\nabla \cdot \nabla V$$

Thus, in Cartesian coordinates,

$$\text{Laplacian } V = \nabla \cdot \nabla V = \nabla^2 V$$

$$\nabla^2 V = \frac{\partial^2 V}{\partial x^2} + \frac{\partial^2 V}{\partial y^2} + \frac{\partial^2 V}{\partial z^2}$$

EXAMPLE 3.11

Find the Laplacian of the scalar fields of Example 3.3; that is,

(a) $V = e^{-z} \sin 2x \cosh y$

(b) $U = \rho^2 z \cos 2\phi$

$$a) \nabla^2 V = \frac{\partial^2 V}{\partial x^2} + \frac{\partial^2 V}{\partial y^2} + \frac{\partial^2 V}{\partial z^2}$$

$$= \frac{\partial}{\partial x} (2 \cos 2x e^{-z} \cosh y) + \frac{\partial}{\partial y} (e^{-z} \sin 2x \sinh y)$$

$$+ \frac{\partial}{\partial z} (-\sin 2x \cosh y e^{-z})$$

$$= -4 \sin 2x e^{-z} \cosh y + e^{-z} \sin 2x \cosh y + \sin 2x \cosh y e^{-z}$$

$$\nabla^2 V = -2 \sin 2x \cosh y e^{-z}$$

$$b) U = \rho^2 z \cos 2\phi$$

$$\nabla U = \frac{\partial U}{\partial \rho} \hat{\rho} + \frac{1}{\rho} \frac{\partial U}{\partial \phi} \hat{\phi} + \frac{\partial U}{\partial z} \hat{z}$$

$$= 2\rho z \cos 2\phi \hat{\rho} - 2\rho z \sin 2\phi \hat{\phi} + \rho^2 \cos 2\phi \hat{z}$$

$$\nabla \cdot A = \frac{1}{\rho} \frac{\partial \rho A_\rho}{\partial \rho} + \frac{1}{\rho} \frac{\partial A_\phi}{\partial \phi} + \frac{\partial A_z}{\partial z}$$

$$\nabla \cdot \nabla U = \frac{1}{\rho} \frac{\partial}{\partial \rho} (2\rho^2 z \cos 2\phi) + \frac{1}{\rho} \frac{\partial}{\partial \phi} (-2\rho z \sin 2\phi) + \frac{\partial}{\partial z} (\rho^2 \cos 2\phi)$$

$$\frac{1}{\rho} [4\rho z \cos 2\phi] - \frac{1}{\rho} [-4\rho z \cos 2\phi] + 0$$

$$\nabla^2 U = 4z \cos 2\phi + 4z \cos 2\phi$$

EXAMPLE 3.10

For a vector field $\mathbf{A}$, show explicitly that $\nabla \cdot \nabla \times \mathbf{A} = 0$; that is, the divergence of the curl of any vector field is zero.

Solution:

This vector identity along with the one in Practice Exercise 3.10 is very useful in EM. For simplicity, assume that $\mathbf{A}$ is in Cartesian coordinates.

$$\begin{aligned}
 \nabla \cdot \nabla \times \mathbf{A} &= \left(\frac{\partial}{\partial x}, \frac{\partial}{\partial y}, \frac{\partial}{\partial z} \right) \cdot \begin{vmatrix} \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ A_x & A_y & A_z \end{vmatrix} \\
 &= \left(\frac{\partial}{\partial x}, \frac{\partial}{\partial y}, \frac{\partial}{\partial z} \right) \cdot \left[\left(\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right), - \left(\frac{\partial A_z}{\partial x} - \frac{\partial A_x}{\partial z} \right), \left(\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right) \right] \\
 &= \frac{\partial}{\partial x} \left(\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right) - \frac{\partial}{\partial y} \left(\frac{\partial A_z}{\partial x} - \frac{\partial A_x}{\partial z} \right) + \frac{\partial}{\partial z} \left(\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right) \\
 &= \frac{\partial^2 A_z}{\partial x \partial y} - \frac{\partial^2 A_y}{\partial x \partial z} - \frac{\partial^2 A_z}{\partial y \partial x} + \frac{\partial^2 A_x}{\partial y \partial z} + \frac{\partial^2 A_y}{\partial z \partial x} - \frac{\partial^2 A_x}{\partial z \partial y} \\
 &= 0
 \end{aligned}$$

PRACTICE EXERCISE 3.10

For a scalar field V , show that $\nabla \times \nabla V = 0$; that is, the curl of the gradient of any scalar field vanishes.

Answer: Proof.

Example

$$\nabla \times A = \begin{vmatrix} a_x & a_y & a_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ A_x & A_y & A_z \end{vmatrix}$$

$$\nabla \times A = \left[\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right] a_x - \left[\frac{\partial A_z}{\partial x} - \frac{\partial A_x}{\partial z} \right] a_y + \left[\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right] a_z$$

$$\nabla \cdot \rho = \frac{\partial \rho_x}{\partial x} + \frac{\partial \rho_y}{\partial y} + \frac{\partial \rho_z}{\partial z}$$

$$= \frac{\partial}{\partial x} \left[\frac{\partial A_z}{\partial y} - \frac{\partial A_y}{\partial z} \right] + \frac{\partial}{\partial y} \left[-\frac{\partial A_z}{\partial x} + \frac{\partial A_x}{\partial z} \right]$$

$$+ \frac{\partial}{\partial z} \left[\frac{\partial A_y}{\partial x} - \frac{\partial A_x}{\partial y} \right]$$

$$= \frac{\partial^2 A_z}{\partial x \partial y} - \frac{\partial^2 A_y}{\partial x \partial z} - \frac{\partial^2 A_z}{\partial y \partial x} + \frac{\partial^2 A_x}{\partial y \partial z} + \frac{\partial^2 A_y}{\partial z \partial x} - \frac{\partial^2 A_x}{\partial z \partial y}$$

$$= \text{Zero}$$

PRACTICE EXERCISE 3.10

For a scalar field V , show that $\nabla \times \nabla V = 0$; that is, the curl of the gradient of any scalar field vanishes.

(A_x, A_y, A_z)

Answer: Proof.

$$\nabla V = \frac{\partial V}{\partial x} \hat{a}_x + \frac{\partial V}{\partial y} \hat{a}_y + \frac{\partial V}{\partial z} \hat{a}_z$$

$$\nabla \times \nabla V = \begin{vmatrix} \hat{a}_x & \hat{a}_y & \hat{a}_z \\ \frac{\partial}{\partial x} & \frac{\partial}{\partial y} & \frac{\partial}{\partial z} \\ \frac{\partial V}{\partial x} & \frac{\partial V}{\partial y} & \frac{\partial V}{\partial z} \end{vmatrix}$$

$$= \left[\frac{\partial^2 V}{\partial y \partial z} - \frac{\partial^2 V}{\partial z \partial y} \right] \hat{a}_x - \left[\frac{\partial^2 V}{\partial x \partial z} - \frac{\partial^2 V}{\partial z \partial x} \right] \hat{a}_y$$

$$+ \left[\frac{\partial^2 V}{\partial x \partial y} - \frac{\partial^2 V}{\partial y \partial x} \right] \hat{a}_z$$

$$= 0 \hat{a}_x + 0 \hat{a}_y + 0 \hat{a}_z$$

$$= 0$$